


- SPECIFICATIONS:
- *ELECTROMAGNETIC ACTUATION
 - *220V VOLTAGE
 - *KF40 PORT FLANGES
 - *VITON SEAL
 - *VACUUM RANGE: 1 X 10-8 TORR
 - *BAKE TEMPERATURE: 150°C (302°F)
 - *SST EXPOSED TO VACUUM
 - *OPENS AND SEALS AGAINST ATMOSPHERE
 - *HIGH RELIABILITY
 - *304 SST CONSTRUCTION

NOTE:
1. DIMENSIONS IN [X.XX] ARE IN mm.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
TLI ENTERPRISES, INC. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
THERMIONICS LABORATORY INC. IS
PROHIBITED.

<div>DIMENSIONS ARE IN INCHES</div> <div>TOLERANCES:</div> <div>FRACTIONAL ± N/A</div> <div>ANGULAR: MACH ± BEND ± 5°</div> <div>ONE PLACE DECIMAL ± .1</div> <div>TWO PLACE DECIMAL ± .01</div> <div>THREE PLACE DECIMAL ± .005</div> <div>SURFACE FINISH 63 R.M.S.</div>		FINISH:		<div></div> <div>thermionics</div> <div>laboratory, inc.</div>		DO NOT SCALE DRAWING		REVISION			
						<div><i>thermionics laboratory inc.</i></div> <div><i>3118 Depot Rd., Hayward Ca. 94545</i></div>					
	NAME	SIGNATURE	DATE		USED ON	NEXT ASSY.	<div>TITLE:</div> <div><i>ELECTROMAGNETIC ANGLE VALVE,</i></div> <div><i>KF40, VITON BONNET,</i></div> <div><i>OUTLINE DRAWING</i></div>				
DESIGN/ENG.						GEN. USE					
CHK'D											
APPV'D											
MFG											
Q.A				MATERIAL:		DWG NO.				A3	
						A-200-EM-KF40					
				WEIGHT:		SCALE:1:3				SHEET 1 OF 1	

A-200-EM-KF40

A3