


- SPECIFICATIONS:
- *ELECTROMAGNETIC ACTUATION
 - *220V VOLTAGE
 - *KF40 PORT FLANGES
 - *VITON SEAL
 - *VACUUM RANGE: 1 X 10⁻⁸ TORR
 - *BAKE TEMPERATURE: 150 °C (302 °F)
 - *SST EXPOSED TO VACUUM
 - *OPENS AND SEALS AGAINST ATMOSPHERE
 - *HIGH RELIABILITY
 - *304 SST CONSTRUCTION

NOTE:
1. DIMENSIONS IN [X.XX] ARE IN mm.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
TLI ENTERPRISES, INC. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
THERMIONICS LABORATORY INC. IS
PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± N/A ANGULAR: MACH ± BEND ± .5° ONE PLACE DECIMAL ± .1 TWO PLACE DECIMAL ± .01 THREE PLACE DECIMAL ± .005 SURFACE FINISH 63 R.M.S.				FINISH:		<div></div> <div>thermionics laboratory, inc.</div>		DO NOT SCALE DRAWING		REVISION	
<div>thermionics laboratory inc. 3118 Depot Rd., Hayward Ca. 94545</div>											
		NAME	SIGNATURE	DATE		USED ON	NEXT ASSY.	TITLE: <div>ELECTROMAGNETIC INLINE VALVE, KF40, VITON BONNET, OUTLINE DRAWING</div>			
DESIGN/ENG.							GEN. USE				
CHK'D											
APPV'D											
MFG											
Q.A						MATERIAL:		DWG NO.		A3	
								TL-1500-EM-KF40-SST			
						WEIGHT:		SCALE:1:3		SHEET 1 OF 1	