









SPECIFICATIONS:
*PORT: 1.13" TUBE
*MATERIALS:
BODY: 304 SST, ELECTROPOLISHED
BELLOWS: WELDED AM-350 SST
BONNET SEAL: Cu
POPPET SEAL: VITON
OTHER MATERIALS AVAILABLE
ACTUATION: SELF-LUBRICATING BRONZE NUTS
WITH ACME THREADS
DIFFERENTIAL PRESSURE: MAXIMUM 20 PSIA ACROSS VALVE SEAT
VACUUM RANGE: COPPER BONNET SEAL: ≥ $1x10^{-10}$ UHV

NOTES:
1. ALL WELDS TO BE VAC. TIGHT TO $2x10^{-10}$ MIN. SENSITIVITY.
2. DIMENSIONS IN [X.XX] ARE IN mm.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF THERMIONICS LABORATORY INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF THERMIONICS LABORATORY INC. IS PROHIBITED.

DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL ± N/A
ANGULAR: MACH ± BEND ±.5°
ONE PLACE DECIMAL ±.1
TWO PLACE DECIMAL ±.01
THREE PLACE DECIMAL ±.005
SURFACE FINISH 63 R.M.S.

FINISH:

DO NOT SCALE DRAWING | REVISION

thermionics laboratory inc.
Hayward Ca. 94545

	NAME	SIGNATURE	DATE		USED ON	NEXT ASSY.
DESIGN/ENG.						GEN. USE
CHK'D						
APPV'D						
MFG						
Q.A						

TITLE:
STRAIGHT THROUGH VALVE

MATERIAL:

DWG NO. SVV-112-20 | A3

WEIGHT: | SCALE:1:2 | SHEET 1 OF 1